PYROSAFE WB

Pyrosafe WB is a water based intumescent fire-retardant coating which provides excellent protection to structural steel.

Pyrosafe WB can also be used as a fire protective coating on wood and electrical cables.

PROPERTIES:

1. Excellent fire protection properties
2. Increases the stability of steel for up to 60 minutes
3. Reduces the flame spread along combustible substances
4. Non-toxic
5. Easy to apply with brush, roller, or spray
6. Excellent adhesive properties

TECHNICAL DATA:

Viscosity	:	135 – 140 KU
S.G.	:	1.20 – 1.30
Type	:	Water-based
Solids by Volume	:	50.5%
Solids by Weight	:	60.0%
Gloss Level	:	Matt
Flash Point	:	Nil
Drying Time at 25°C	:	Surface Dry - 1 Hour
	:	Hand Dry - 6 Hours
Recoating	:	After 6 Hours
Recommended DFT	:	Dependent on the substrate
Packaging	:	Single pack 5 litres and 25 litres
Colour	:	White
Shelf Life	:	12 months in unopened containers

APPLICATION:

Stir well before use. Apply with brush, roller, or spray. Thinning not recommended. Clean up- water.

The information and recommendations presented on this data sheet are to the best of our knowledge and belief accurate and reliable, but do not constitute a warrant. None of our representatives or agents are authorized to give any guarantee or warrantee or make any representation in addition or contrary to the above, and we not accept liability for claims of any kind for any loss including, without limitation, consequential loss injury or damage arising from the use of the information on recommendation, or of the products which are the subject matter hereof. These products are sold subject to our standard conditions of sale and tender, copies of which are available on request.