VIP PLASTER

PHYSICAL PROPERTIES

VIP Plaster is a white gypsum-based plaster for skimming ceilings and for use in crack/openings in walls. Also used for penetration and conduit casings (interior use only).

APPLICATION:

VIP Plaster may be mixed by hand or mechanically for a minimum of 3 minutes. Plaster into dampened areas. Use a straight edge steel float to finish.

Setting time	:	Minimum 45 minutes
	:	Maximum 5.5 hours
Colour	:	White
Shelf life	:	12 months
Storage	:	Keep dry until ready to use
Packaging	:	25 kg/bag
Dry bulk density	:	650 kg/m650 kg/m³

SAFETY

There are no known health hazards and normal precaution relevant to the handling of gypsum-based products applies. I.e. dust masks, eye protection and covering of sensitive skin. VIP Plaster does not contain asbestos.

The information and recommendations presented on this data sheet are to the best of our knowledge and belief accurate and reliable, but do not constitute a warrant. None of our representatives or agents are authorized to give any guarantee or warrantee or make any representation in addition or contrary to the above, and we not accept liability for claims of any kind for any loss including, without limitation, consequential loss injury or damage arising from the use of the information on recommendation, or of the products which are the subject matter hereof. These products are sold subject to our standard conditions of sale and tender, copies of which are available on request.